

Escarfagem Externa de cordão de solda - Insertos Quadrados - Positiva

Especificação	d	s	r	d ₁	A	R	Diâmetro Mín.	Diâmetro Máx.
	mm	mm	mm	mm	mm	mm	mm	mm
SNMX-1507-22-R07	15,87	7,94	0,8	6,35	7	22	9,80	12,60
SNMX-1507-22-R09	15,87	7,94	0,8	6,35	9	22	12,60	15,88
SNMX-1507-22-R10	15,87	7,94	0,8	6,35	10	22	13,30	17,20
SNMX-1507-22-R13	15,87	7,94	0,8	6,35	13	22	15,88	22,23
SNMX-1507-22-R15	15,87	7,94	0,8	6,35	15	22	18,90	27,60
SNMX-1507-22-R18	15,87	7,94	0,8	6,35	18	22	25,20	33,12
SNMX-1507-22-R20	15,87	7,94	0,8	6,35	20	22	28,00	36,80
SNMX-1507-22-R22	15,87	7,94	0,8	6,35	22	22	30,90	39,60
SNMX-1507-22-R25	15,87	7,94	0,8	6,35	25	22	35,00	41,25
SNMX-1507-22-R27	15,87	7,94	0,8	6,35	27	22	41,28	50,80
SNMX-1507-22-R30	15,87	7,94	0,8	6,35	30	22	42,00	55,20
SNMX-1507-22-R35	15,87	7,94	0,8	6,35	35	22	49,00	64,40
SNMX-1507-22-R40	15,87	7,94	0,8	6,35	40	22	56,00	73,60
SNMX-1507-22-R42	15,87	7,94	0,8	6,35	42	22	59,00	77,50
SNMX-1507-22-R45	15,87	7,94	0,8	6,35	45	22	63,00	82,80
SNMX-1507-22-R50	15,87	7,94	0,8	6,35	50	22	75,00	92,08
SNMX-1507-22-R55	15,87	7,94	0,8	6,35	55	22	83,50	104,70
SNMX-1507-22-R60	15,87	7,94	0,8	6,35	60	22	92,08	117,40
SNMX-1507-22-R65	15,87	7,94	0,8	6,35	65	22	100,66	125,60
SNMX-1507-22-R70	15,87	7,94	0,8	6,35	70	22	109,24	136,20
SNMX-1507-22-R75	15,87	7,94	0,8	6,35	75	22	117,82	145,70
SNMX-1907-22-R00	19,05	7,94	1,2	6,35	0	35	sem raio - uso em tubos Ø grande	
SNMX-1907-22-R10	19,05	7,94	1,2	6,35	10	35	14,00	18,90
SNMX-1907-22-R12	19,05	7,94	1,2	6,35	12	35	15,88	22,33
SNMX-1907-22-R15	19,05	7,94	1,2	6,35	15	35	18,90	27,60
SNMX-1907-22-R20	19,05	7,94	1,2	6,35	20	35	28,00	36,80
SNMX-1907-22-R25	19,05	7,94	1,2	6,35	25	35	35,00	41,28
SNMX-1907-22-R35	19,05	7,94	1,2	6,35	35	35	49,00	64,40
SNMX-1907-22-R45	19,05	7,94	1,2	6,35	45	35	63,00	82,80
SNMX-1907-22-R55	19,05	7,94	1,2	6,35	55	35	82,50	97,50
SNMX-1907-22-R60	19,05	7,94	1,2	6,35	60	35	92,08	117,48
SNMX-2512-22-R00	25,40	12,70	0,8	9,12	0	48	sem raio - uso em tubos Ø grande	
SNMX-2512-22-R25	25,40	12,70	0,8	9,12	25	48	35,00	41,25
SNMX-2512-22-R35	25,40	12,70	0,8	9,12	35	48	49,00	64,40
SNMX-2512-22-R50	25,40	12,70	0,8	9,12	50	48	75,00	92,08
SNMX-2512-22-R65	25,40	12,70	0,8	9,12	65	48	97,50	120,00
SNMX-2512-22-R80	25,40	12,70	0,8	9,12	80	48	120,00	147,20
SNMX-2512-22-R90	25,40	12,70	0,8	9,12	90	48	135,00	171,00
SNMX-2512-22-R100	25,40	12,70	0,8	9,12	100	48	150,00	190,00
SNMX-2512-22-R120	25,40	12,70	0,8	9,12	120	48	180,00	228,00
SNMX-2512-22-R150	25,40	12,70	0,8	9,12	150	48	225,00	285,00
SNMX-2512-22-R200	25,40	12,70	0,8	9,12	200	48	300,00	380,00
SNMX-2512-22-R250	25,40	12,70	0,8	9,12	250	48	375,00	475,00

